
# Challenges/Problems Yet-to-be Addressed Before the Construction of the ILC (my personal view)

Masakazu Yoshioka (KEK Professor Emeritus)
Since 2013, my position is Tohoku/Iwate University
Tohoku ILC Promotion Council/Tohoku ILC Preparation Office

Jan 25 2018





### Remind about the ILC in Kitakami candidate site

Basic policy of the ILC construction: Staging scenario

 $20.5 \text{km} \Rightarrow 31 \text{km} \Rightarrow 50 \text{km}$  $250 \text{GeV} \Rightarrow 500 \text{GeV} \Rightarrow 1 \text{TeV}$ 

The Kitakami candidate site has a potential to accept the 50km ILC









Shin Michizono (22 Jan 2018, ILC Status)


(20.5km)

## Location












Table 5-1: New beam parameters optimized for II C250GeV.

Collision frequency         Hz         5         5           Electron linac rep rate         Hz         10         5         5           Beam power (2 beams)         P <sub>B</sub> MW         5.26         10.5         5.26           r.m.s. bunch length at IP $\sigma_z$ mm         0.3         0.3         0.3           relative energy spread at IP (e-) $\sigma_E/E$ %         0.188         0.124         0.188           relative energy spread at IP (e+) $\sigma_E/E$ %         0.15         0.07         0.15           Normalized horizontal emittance at IP $\epsilon_{nx}$ µm         10         10         5           Normalized vertical emittance at IP $\epsilon_{nx}$ µm         10         10         5           Normalized vertical emittance at IP $\epsilon_{nx}$ µm         10         10         5           Normalized vertical emittance at IP $\epsilon_{nx}$ µm         10         10         5           Normalized vertical emittance at IP $\epsilon_{nx}$ µm         10         10         5           Beam polarization (e-) $\epsilon_{nx}$ 80         80         80         80           Beat function at IP (	Table 5-1: New beam parameters optimized for ILC250GeV.						
Bunch population         N         e10         2         2         2           Bunch separation         ns         554         554         554           Beam current         mA         5.78         5.78         5.78           Number of bunches per pulse         Nb         1312         1312         1312           Collision frequency         Hz         5         5         5           Electron linac rep rate         Hz         10         5         5           Beam power (2 beams)         PB         MW         5.26         10.5         5.26           r.m.s. bunch length at IP $σ_z$ mm         0.3         0.3         0.3           relative energy spread at IP (e-) $σ_E/E$ %         0.188         0.124         0.188           relative energy spread at IP (e-) $σ_E/E$ %         0.15         0.07         0.15           Normalized horizontal emittance at IP $σ_E/E$ %         0.15         0.07         0.15           Normalized vertical emittance at IP $ε_{nx}$ μm         10         10         5           Beam polarization (e-) $ε_{nx}$ $ε_{nx}$ nm         35				TDR		New	
Bunch separation         ns         554         554         554           Beam current         mA         5.78         5.78         5.78           Number of bunches per pulse         Nb         1312         1312         1312           Collision frequency         Hz         5         5         5           Electron linac rep rate         Hz         10         5         5           Beam power (2 beams)         P <sub>B</sub> MW         5.26         10.5         5.26           r.m.s. bunch length at IP $\sigma_z$ mm         0.3         0.3         0.3           relative energy spread at IP (e-) $\sigma_E/E$ %         0.188         0.124         0.188           relative energy spread at IP (e-) $\sigma_E/E$ %         0.15         0.07         0.15           Normalized horizontal emittance at IP $\sigma_E/E$ %         0.15         0.07         0.15           Normalized vertical emittance at IP $\epsilon_{nx}$ μm         10         10         5           Beam polarization (e-)         %         80         80         80         80           Beam polarization (e+) $\epsilon_{nx}$ mm         13         11	Center-of-mass energy	Есм	GeV	250	500	250	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	Bunch population	N	e10	2	2	2	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	Bunch separation		ns	554	554	554	
Collision frequency         Hz         5         5           Electron linac rep rate         Hz         10         5         5           Beam power (2 beams)         P <sub>B</sub> MW         5.26         10.5         5.26           r.m.s. bunch length at IP $\sigma_z$ mm         0.3         0.3         0.3           relative energy spread at IP (e-) $\sigma_E/E$ %         0.188         0.124         0.188           relative energy spread at IP (e+) $\sigma_E/E$ %         0.15         0.07         0.15           Normalized horizontal emittance at IP $\epsilon_{nx}$ µm         10         10         5           Normalized vertical emittance at IP $\epsilon_{nx}$ µm         10         10         5           Normalized vertical emittance at IP $\epsilon_{nx}$ µm         10         10         5           Normalized vertical emittance at IP $\epsilon_{nx}$ µm         10         10         5           Normalized vertical emittance at IP $\epsilon_{nx}$ µm         10         10         5           Beam polarization (e-) $\epsilon_{nx}$ 80         80         80         80           Beat function at IP (	Beam current		mA	5.78	5.78	5.78	
Electron linac rep rate         Hz         10         5         5           Beam power (2 beams) $P_B$ MW         5.26         10.5         5.26           r.m.s. bunch length at IP $σ_z$ mm         0.3         0.3         0.3           relative energy spread at IP (e-) $σ_E/E$ %         0.158         0.124         0.188           relative energy spread at IP (e+) $σ_E/E$ %         0.15         0.07         0.15           Normalized horizontal emittance at IP $ε_{nx}$ μm         10         10         5           Normalized vertical emittance at IP $ε_{nx}$ μm         10         10         5           Normalized vertical emittance at IP $ε_{nx}$ μm         10         10         5           Normalized vertical emittance at IP $ε_{nx}$ μm         10         10         5           Normalized vertical emittance at IP $ε_{nx}$ μm         10         10         5           Normalized vertical emittance at IP $ε_{nx}$ μm         10         10         30         30         30         30         30         30         30         30	Number of bunches per pulse	Nb		1312	1312	1312	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	Collision frequency		Hz	5	5	5	
r.m.s. bunch length at IP $σ_z$ mm       0.3       0.3       0.3         relative energy spread at IP (e-) $σ_E/E$ %       0.188       0.124       0.188         relative energy spread at IP (e+) $σ_E/E$ %       0.15       0.07       0.15         Normalized horizontal emittance at IP $ε_{nx}$ $μm$ 10       10       5         Normalized vertical emittance at IP $ε_{ny}$ nm       35       35       35         Beam polarization (e-)       %       80       80       80         Beam polarization (e+)       %       30       30       30         Beta function at IP (x) $β_x$ mm       13       11       13         Beta function at IP (y) $β_y$ mm       0.41       0.48       0.41         r.m.s. beam size at IP (y) $σ_x$ nm       7.29       474       516         r.m.s. beam angle spread at IP (x) $σ_y$ μr       56.1       43.1       39.7         r.m.s. beam angle spread at IP (y) $θ_y$ μr       18.7       12.2       18.7         Disruption parameter (x)       Dx       0.26       0.26       0.51 <tr< td=""><td>Electron linac rep rate</td><td></td><td>Hz</td><td>10</td><td>5</td><td>5</td></tr<>	Electron linac rep rate		Hz	10	5	5	
relative energy spread at IP (e-) $\sigma_E/E$ % 0.188 0.124 0.188 relative energy spread at IP (e+) $\sigma_E/E$ % 0.15 0.07 0.15 Normalized horizontal emittance at IP $\epsilon_{nx}$ $\mu m$ 10 10 5 Normalized vertical emittance at IP $\epsilon_{ny}$ nm 35 35 35 35 Beam polarization (e-) % 80 80 80 80 80 Beam polarization (e+) % 30 30 30 30 Beta function at IP (x) $\beta_x$ mm 13 11 13 Beta function at IP (y) $\beta_y$ mm 0.41 0.48 0.41 r.m.s. beam size at IP (x) $\sigma_x$ nm 729 474 516 r.m.s. beam size at IP (y) $\sigma_y$ nm 7.66 5.86 7.66 r.m.s. beam angle spread at IP (x) $\theta_x$ $\mu$ r 56.1 43.1 39.7 r.m.s. beam angle spread at IP (y) $\theta_y$ $\mu$ r 18.7 12.2 18.7 Disruption parameter (x) Dx 0.26 0.26 0.51 Disruption parameter (y) Dy 24.5 24.6 34.5 Upsilon (average) Y 0.020 0.062 0.028 Geometric luminosity Lgeo e34/cm²s 0.374 0.751 0.528 Geometric luminosity	Beam power (2 beams)	P <sub>B</sub>	MW	5.26	10.5	5.26	
relative energy spread at IP (e+) $\sigma_{E}/E$ % 0.15 0.07 0.15 Normalized horizontal emittance at IP $\epsilon_{nx}$ $\mu m$ 10 10 5 Normalized vertical emittance at IP $\epsilon_{ny}$ nm 35 35 35 35 Beam polarization (e-) % 80 80 80 80 Beam polarization (e+) % 30 30 30 30 Beta function at IP (x) $\beta_{x}$ mm 13 11 13 Beta function at IP (y) $\beta_{y}$ mm 0.41 0.48 0.41 r.m.s. beam size at IP (x) $\sigma_{x}$ nm 729 474 516 r.m.s. beam size at IP (y) $\sigma_{y}$ nm 7.66 5.86 7.66 r.m.s. beam angle spread at IP (x) $\theta_{x}$ $\mu r$ 56.1 43.1 39.7 r.m.s. beam angle spread at IP (y) $\theta_{y}$ $\mu r$ 18.7 12.2 18.7 Disruption parameter (x) Dx 0.26 0.26 0.51 Disruption parameter (y) Dy 24.5 24.6 34.5 Upsilon (average) Y 0.020 0.062 0.028 Number of beamstrahlung photons $n_{\gamma}$ 1.21 1.82 1.91 Energy loss by beamstrahlung $\delta_{BS}$ % 0.97 4.50 2.62 Geometric luminosity Lgeo e34/cm²s 0.374 0.751 0.528	r.m.s. bunch length at IP	$\sigma_{z}$	mm	0.3	0.3	0.3	
Normalized horizontal emittance at IP $ε_{nx}$ μm         10         10         5           Normalized vertical emittance at IP $ε_{ny}$ nm         35         35         35           Beam polarization (e-)         %         80         80         80           Beam polarization (e+)         %         30         30         30           Beta function at IP (x) $β_x$ mm         13         11         13           Beta function at IP (y) $β_y$ mm         0.41         0.48         0.41           r.m.s. beam size at IP (y) $σ_x$ nm         729         474         516           r.m.s. beam size at IP (y) $σ_y$ nm         7.66         5.86         7.66           r.m.s. beam angle spread at IP (x) $θ_x$ μr         56.1         43.1         39.7           r.m.s. beam angle spread at IP (y) $θ_y$ μr         18.7         12.2         18.7           Disruption parameter (x)         Dx         0.26         0.26         0.51           Disruption parameter (y)         Dy         24.5         24.6         34.5           Upsilon (average)         Y         0.020 </td <td>relative energy spread at IP (e-)</td> <td><math>\sigma_{E}/E</math></td> <td>%</td> <td>0.188</td> <td>0.124</td> <td>0.188</td>	relative energy spread at IP (e-)	$\sigma_{E}/E$	%	0.188	0.124	0.188	
IP $ε_{nx}$ μm         10         10         5           Normalized vertical emittance at IP $ε_{ny}$ nm         35         35         35           Beam polarization (e-)         %         80         80         80           Beam polarization (e+)         %         30         30         30           Beta function at IP (x) $β_x$ mm         13         11         13           Beta function at IP (y) $β_y$ mm         0.41         0.48         0.41           r.m.s. beam size at IP (y) $σ_x$ nm         729         474         516           r.m.s. beam size at IP (y) $σ_y$ nm         7.66         5.86         7.66           r.m.s. beam angle spread at IP (x) $θ_x$ μr         56.1         43.1         39.7           r.m.s. beam angle spread at IP (y) $θ_y$ μr         18.7         12.2         18.7           Disruption parameter (x)         Dx         0.26         0.26         0.51           Disruption parameter (y)         Dy         24.5         24.6         34.5           Upsilon (average)         Y         0.020         0.062	relative energy spread at IP (e+)	$\sigma_{E}/E$	%	0.15	0.07	0.15	
Normalized vertical emittance at IP $ε_{ny}$ nm         35         35           Beam polarization (e-)         %         80         80         80           Beam polarization (e+)         %         30         30         30           Beta function at IP (x) $β_x$ mm         13         11         13           Beta function at IP (y) $β_y$ mm         0.41         0.48         0.41           r.m.s. beam size at IP (x) $σ_x$ nm         729         474         516           r.m.s. beam size at IP (y) $σ_y$ nm         7.66         5.86         7.66           r.m.s. beam angle spread at IP (x) $θ_x$ μr         56.1         43.1         39.7           r.m.s. beam angle spread at IP (y) $θ_y$ μr         18.7         12.2         18.7           Disruption parameter (x)         Dx         0.26         0.26         0.51           Disruption parameter (y)         Dy         24.5         24.6         34.5           Upsilon (average)         Y         0.020         0.062         0.028           Number of beamstrahlung photons $η_y$ 1.21         1.82         1.	Normalized horizontal emittance at						
Beam polarization (e-)       %       80       80       80         Beam polarization (e+)       %       30       30       30         Beta function at IP (x) $β_x$ mm       13       11       13         Beta function at IP (y) $β_y$ mm       0.41       0.48       0.41         r.m.s. beam size at IP (x) $σ_x$ nm       729       474       516         r.m.s. beam size at IP (y) $σ_y$ nm       7.66       5.86       7.66         r.m.s. beam angle spread at IP (x) $θ_x$ $µr$ 56.1       43.1       39.7         r.m.s. beam angle spread at IP (y) $θ_y$ $µr$ 18.7       12.2       18.7         Disruption parameter (x) $Dx$ $0.26$ $0.26$ $0.51$ Disruption parameter (y) $Dy$ $24.5$ $24.6$ $34.5$ Upsilon (average) $Y$ $0.020$ $0.062$ $0.028$ Number of beamstrahlung photons $n_\gamma$ $1.21$ $1.82$ $1.91$ Energy loss by beamstrahlung $δ_{BS}$ $%$ $0.374$ $0.751$ $0.528$ Geometric luminosity <t< td=""><td>IP</td><td>ε<sub>nx</sub></td><td>μm</td><td>10</td><td>10</td><td>5</td></t<>	IP	ε <sub>nx</sub>	μm	10	10	5	
Beam polarization (e+)       %       30       30       30         Beta function at IP (x) $β_x$ mm       13       11       13         Beta function at IP (y) $β_y$ mm       0.41       0.48       0.41         r.m.s. beam size at IP (x) $σ_x$ nm       729       474       516         r.m.s. beam size at IP (y) $σ_y$ nm       7.66       5.86       7.66         r.m.s. beam angle spread at IP (x) $θ_x$ μr       56.1       43.1       39.7         r.m.s. beam angle spread at IP (y) $θ_y$ μr       18.7       12.2       18.7         Disruption parameter (x)       Dx       0.26       0.26       0.51         Disruption parameter (y)       Dy       24.5       24.6       34.5         Upsilon (average)       Y       0.020       0.062       0.028         Number of beamstrahlung photons $n_\gamma$ 1.21       1.82       1.91         Energy loss by beamstrahlung $δ_{BS}$ %       0.97       4.50       2.62         Geometric luminosity       Lgeo       e34/cm²s       0.374       0.751       0.529	Normalized vertical emittance at IP	ε <sub>ny</sub>	nm	35	35	35	
Beta function at IP (x) $β_x$ mm         13         11         13           Beta function at IP (y) $β_y$ mm         0.41         0.48         0.41           r.m.s. beam size at IP (x) $σ_x$ nm         729         474         516           r.m.s. beam size at IP (y) $σ_y$ nm         7.66         5.86         7.66           r.m.s. beam angle spread at IP (x) $θ_x$ μr         56.1         43.1         39.7           r.m.s. beam angle spread at IP (y) $θ_y$ μr         18.7         12.2         18.7           Disruption parameter (x)         Dx         0.26         0.26         0.51           Disruption parameter (y)         Dy         24.5         24.6         34.5           Upsilon (average)         Y         0.020         0.062         0.028           Number of beamstrahlung photons $n_\gamma$ 1.21         1.82         1.91           Energy loss by beamstrahlung $δ_{BS}$ %         0.97         4.50         2.62           Geometric luminosity         Lgeo         e34/cm²s         0.374         0.751         0.529	Beam polarization (e-)		%	80	80	80	
Beta function at IP (y) $β_y$ mm       0.41       0.48       0.41         r.m.s. beam size at IP (x) $σ_x$ nm       729       474       516         r.m.s. beam size at IP (y) $σ_y$ nm       7.66       5.86       7.66         r.m.s. beam angle spread at IP (x) $θ_x$ $μr$ 56.1       43.1       39.7         r.m.s. beam angle spread at IP (y) $θ_y$ $μr$ 18.7       12.2       18.7         Disruption parameter (x)       Dx       0.26       0.26       0.51         Disruption parameter (y)       Dy       24.5       24.6       34.5         Upsilon (average)       Y       0.020       0.062       0.028         Number of beamstrahlung photons $η_γ$ 1.21       1.82       1.91         Energy loss by beamstrahlung $δ_{BS}$ %       0.97       4.50       2.62         Geometric luminosity       Lgeo       e34/cm²s       0.374       0.751       0.529	Beam polarization (e+)		%	30	30	30	
r.m.s. beam size at IP (x) $σ_x$ nm       729       474       516         r.m.s. beam size at IP (y) $σ_y$ nm       7.66       5.86       7.66         r.m.s. beam angle spread at IP (x) $θ_x$ $µr$ 56.1       43.1       39.7         r.m.s. beam angle spread at IP (y) $θ_y$ $µr$ 18.7       12.2       18.7         Disruption parameter (x) $Dx$ 0.26       0.26       0.51         Disruption parameter (y) $Dy$ 24.5       24.6       34.5         Upsilon (average) $Y$ 0.020       0.062       0.028         Number of beamstrahlung photons $n_\gamma$ 1.21       1.82       1.91         Energy loss by beamstrahlung $δ_{BS}$ %       0.97       4.50       2.62         Geometric luminosity       Lgeo       e34/cm²s       0.374       0.751       0.529	Beta function at IP (x)	$\beta_{x}$	mm	13	11	13	
r.m.s. beam size at IP (y) $σ_y$ nm       7.66       5.86       7.66         r.m.s. beam angle spread at IP (x) $θ_x$ $µr$ 56.1       43.1       39.7         r.m.s. beam angle spread at IP (y) $θ_y$ $µr$ 18.7       12.2       18.7         Disruption parameter (x)       Dx       0.26       0.26       0.51         Disruption parameter (y)       Dy       24.5       24.6       34.5         Upsilon (average)       Y       0.020       0.062       0.028         Number of beamstrahlung photons $n_\gamma$ 1.21       1.82       1.91         Energy loss by beamstrahlung $δ_{BS}$ %       0.97       4.50       2.62         Geometric luminosity       Lgeo       e34/cm²s       0.374       0.751       0.529	Beta function at IP (y)	$\beta_{y}$	mm	0.41	0.48	0.41	
r.m.s. beam angle spread at IP (x) $\theta_x$ $\mu r$ 56.1 43.1 39.7 r.m.s. beam angle spread at IP (y) $\theta_y$ $\mu r$ 18.7 12.2 18.7 Disruption parameter (x) Dx 0.26 0.26 0.51 Disruption parameter (y) Dy 24.5 24.6 34.5 Upsilon (average) Y 0.020 0.062 0.028 Number of beamstrahlung photons $n_\gamma$ 1.21 1.82 1.91 Energy loss by beamstrahlung $\delta_{BS}$ % 0.97 4.50 2.62 Geometric luminosity Lgeo e34/cm²s 0.374 0.751 0.529	r.m.s. beam size at IP (x)	$\sigma_{x}$	nm	729	474	516	
r.m.s. beam angle spread at IP (y) $\theta_y$ μr       18.7       12.2       18.7         Disruption parameter (x)       Dx       0.26       0.26       0.51         Disruption parameter (y)       Dy       24.5       24.6       34.5         Upsilon (average)       Y       0.020       0.062       0.028         Number of beamstrahlung photons $n_\gamma$ 1.21       1.82       1.91         Energy loss by beamstrahlung $\delta_{BS}$ %       0.97       4.50       2.62         Geometric luminosity       Lgeo       e34/cm²s       0.374       0.751       0.529	r.m.s. beam size at IP (y)	$\sigma_{y}$	nm	7.66	5.86	7.66	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	r.m.s. beam angle spread at IP (x)	$\theta_{x}$	μr	56.1	43.1	39.7	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	r.m.s. beam angle spread at IP (y)	$\theta_{y}$	μr	18.7	12.2	18.7	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	Disruption parameter (x)	Dx		0.26	0.26	0.51	
Number of beamstrahlung photons $n_{\gamma}$ 1.21 1.82 1.91 Energy loss by beamstrahlung $\delta_{BS}$ % 0.97 4.50 2.62 Geometric luminosity Lgeo e34/cm²s 0.374 0.751 0.529	Disruption parameter (y)	Dy		24.5	24.6	34.5	
Energy loss by beamstrahlung $\delta_{BS}$ % 0.97 4.50 2.62 Geometric luminosity Lgeo e34/cm²s 0.374 0.751 0.529	Upsilon (average)	Y		0.020	0.062	0.028	
Geometric luminosity Lgeo e34/cm²s 0.374 0.751 0.529	Number of beamstrahlung photons	nγ		1.21	1.82	1.91	
Geometric luminosity Lgeo e34/cm²s 0.374 0.751 0.529	Energy loss by beamstrahlung	$\delta_{ extsf{BS}}$	%	0.97	4.50	2.62	
	Geometric luminosity		e34/cm²s	0.374	0.751	0.529	
	Luminosity	L	e34/cm <sup>2</sup> s	0.82	1.79	1.35	

### The International Linear Collider Machine Staging Report 2017 Addendum to the International Linear Collider Technical Design Report published in 2013

KEK 2017-3 **DESY 17-180** CERN-ACC-2017-0097

 $\mathsf{E}_{\mathsf{cm}}$ 250 GeV

Luminosity 1.35 e34/cm<sup>2</sup>/s

with pol. e-

Beam power 5.26 MW (2 beams)

Wall plug power

117.3 MW




#### LCC international structure

Match cooperation between following four sectors in Japan is well functioning toward getting green light hopefully this year

- Academic society (JAHEP: Japan Association of High Energy Physics)
- Political sector (Federation of diet members>150)
- Bureaucracy (MEXT: Experts meetings for FSs)
- Industry sector (AAA: Advanced Accelerator Association Promoting Science & Technology >100)

#### Preliminary international discussion

- Japan/US
- Japan/France
- Japan/Germany
- ACFA (Asian Committee for Future Accelerator)





#### ILC Local structure in Tohoku

- Tohoku ILC Promotion Council
  - Academy, Tohoku Economy Federation and local governments
- Tohoku ILC Preparation Office Headed by Atsuto Suzuki ⇒site specific design 8

#### ICFA Statement on the ILC Operating at 250 GeV as a Higgs Boson Factory

The discovery of a Higgs boson in 2012 at the Large Hadron Collider (LHC) at CERN is one of the most significant recent breakthroughs in science and marks a major step forward in fundamental physics. Precision studies of the Higgs boson will further deepen our understanding of the most fundamental laws of matter and its interactions.

The International Linear Collider (ILC) operating at 250 GeV center
excellent science from precision studies of the Higgs boson. Therefore, ICFA considers the ILC a key

science project complementary to the LHC and its upgrade.

ICFA welcomes the efforts by the Linear Collider Collaboration on cost reductions for the ILC, which indicate that up to 40% cost reduction relative to the 2013 Technical Design Report (500 GeV ILC) is possible for a 250 GeV collider.

ICFA emphasizes the extendibility of the ILC to higher energies and notes that there is large discovery potential with important additional measurements accessible at energies beyond 250 GeV.


ICFA thus supports the conclusions of the Linear Collider Board (LCB) in their report presented at this meeting and very strongly encourages Japan to realize the ILC in a timely fashion as a Higgs boson factory with a center-of-mass energy of 250 GeV as an international project<sup>1</sup>, led by Japanese initiative.

<sup>1</sup>In the LCB report the European XFEL and FAIR are mentioned as recent examples for international projects.

Ottawa, November 2017



# ILC Time Line: Progress and Prospect



### **ILC** status

# KEK/LCC Shin MICHIZONO


- The ILC250
- KEK's activities
- SRF facilities in the world, European XFEL
- ILC cost reduction R&D
- ILC250GeV staging



### Efforts by Tohoku ILC preparation office

- Site specific CFS design in collaboration with KEK
- ◆ Geological survey
  - Boring survey
  - Elastic wave exploration
  - Electrical prospecting
  - Ground survey
  - Hydrological survey

=== We are trying to cover whole area ===



- Environmental impact assessment
- Investigations of various laws and regulations
  - High pressure gas safety law
  - Electricity business act
  - Fire service act
  - Building standards law
  - . . . . . . . .
- Organization of local industry alliance for ILC construction
  - Cost saving
  - Activation of local economy
- Town planning for accepting researchers and their families
- ◆ And many other issues-----

